

NEW PRODUCTS FROM: **PYLE® PRO**

PPHP885A 400 Watts 8" Powered 2 Way Plastic Molded Speaker System

- 8" Woofer
- 1" Titanium Compression Driver
- Xlr Mic Input
- Xlr&Stereo Rca Line Input
- Xlr Line Output
- Master Volume, Bass&Treble Control

- Frequency Response: 45HZ-20KHZ
- Power Output: 200Watts Rms, 400Watts Peak
- Crossover Frequency: 3.0KHZ
- 35MM Speaker Stand Mount
- AC115V-230V
- Dimensions: 13.8"x11.8"x19.3"

UPC Number: 068889007374



PPHP895 400 Watts 8" Powered 2 Way Plastic Molded Speaker System

- 8" Woofer
- 1" Titanium Compression Driver
- Dual 1/4 And Speakon Jacks Input
- 2-Way Ported Enclosure For Extra Bass Response
- Ptc Driver Protect
- Power Max: 400Watts
- Power Rms: 200Watts
- Impedance: 80HM+/-20%

- Sensitivity: 95+/-3DB
- Frequency Response: 45HZ-20KHZ
- Metal Grill To Protect The Woofer/Plastic Cabinet
- Crossover Frequency: 3.0KHZ
- 35MM Speaker Stand Mount
- Dimensions: 13.8"x11.8"x19.3"

UPC Number: 068889007343



PPHP1095 600 Watts 10" Powered 2 Way Plastic Molded Speaker System

- 10" Woofer
- 1" Titanium Compression Driver
- Dual 1/4 And Speakon Jacks Input
- 2-Way Ported Enclosure For Extra Bass Response
- Ptc Driver Protect
- Power Max: 600Watts
- Power Rms: 300Watts
- Impedance: 80HM+/-20%

- Sensitivity: 95+/-3DB
- Frequency Response: 45HZ-20KHZ
- Metal Grill To Protect The Woofer/Plastic Cabinet
- Crossover frequency: 3.0KHZ
- 35MM Speaker Stand Mount
- Dimensions: 15.7"x14.6"x21.3"

UPC Number: 068889007350



PPHP1295 800 Watts 12" Powered 2 Way Plastic Molded Speaker System

- 12" Woofer
- 2.5" Titanium Compression Driver
- Dual 1/4 And Speakon Jacks Input
- 2-Way Ported Enclosure For Extra Bass Response
- Ptc Driver Protect
- Power Max: 800Watts
- Power Rms: 400Watts
- Impedance: 80HM+/-20%

- Sensitivity: 100+/-3DB
- Frequency Response: 45HZ-20KHZ
- Metal Grill To Protect The Woofer/Plastic Cabinet
- Crossover frequency: 3.0KHZ
- 35MM Speaker Stand Mount
- Dimensions: 14.0"x18.5"x25.0"

UPC Number: 068889007367



PPHP1585A 1000 Watts 15" Powered 2 Ways Plastic Molded Speaker system

- 15" Woofer
- 3" Titanium Compression Driver
- Xlr Mic Input
- Xlr&Stereo Rca Line Input
- Xlr Line Output
- Master Volume, Bass&Treble Control
- Frequency Response: 45HZ-20KHZ

- Power Output: 500Watts Rms, 1000Watts Peak
- Crossover Frequency: 3.0KHZ
- 35MM Speaker Stand Mount
- AC115V-230V
- Dimensions: 20.5"x19.0"x29.5"

UPC Number: 068889007404



PPHP1285A 800 Watts 12" Powered 2 Way Plastic Molded Speaker System

- 12" Woofer
- 2.5" Titanium Compression Driver
- Xlr Mic Input
- Xlr&Stereo Rca Line Input
- Xlr Line Output
- Master Volume, Bass&Treble Control
- Frequency Response: 45HZ-20KHZ

- Power Output: 200Watts Rms, 800Watts Peak
- Crossover Frequency: 3.0KHZ
- 35MM Speaker Stand Mount
- AC115V-200V
- Dimensions: 14.0"x18.5"x25.0"

UPC Number: 068889007398



PPHP1085A 600Watts 10" Powered 2 Way Plastic Molded Speaker System

- 10" Woofer
- 1" Titanium Compression Driver
- Xlr Mic Input
- Xlr&Stereo Rca Line Input
- Xlr Line Output
- Master Volume, Bass&Treble Control

- Frequency Response: 45HZ-20KHZ
- Power Output: 300Watts Rms, 600Watts Peak
- Crossover Frequency: 3.0KHZ
- 35MM Speaker Stand Mount
- AC115V-230V
- Dimensions: 15.7"x14.6"x21.3"

UPC Number: 068889007381



1600 63rd Street . Brooklyn . NY . 11204 . 800 444-5671 . Fax: 718 236-2400

www.pyleaudio.com