NEW PRODUCT FROM:

www.pyleaudio.com

PT530A

Two channel 350 Watts Build-In AM/FM Radio Amplifier Receiver

- 2 Channel Amplifier
- Built-In AM/FM Radio
- 2 MIC Input, Treble and Bass of MIC Adjustable. Independent MIC Volume Control.
- Over Current Protection, Short Circuit Protection And Over Voltage Protection
- 12 Preset Radio Station

- Full Remote Control
- VFD Display
- Power Output: 350W for L,R Channel (4 Ohm)
- Input Selector: 3 Stereo RCA Selector, 1AM/FM Radio, 2 Microphone Input
- Output: 2 Channel Speaker Output Terminal for L, R



UPC Number: 068889008821

PT570AU

5.1 channel 350Watts Build-In AM/FM Radio /USB/SD card Amplifier Receiver

- 5.1 Channel Amplifier.
- Built-In AM/FM Radio.
- Built-In USB and SD Audio.
- 2 MIC Input, Treble and Bass of MIC Adjustable, Independent MIC Volume Control
- Over Current Protection, Short Circuit Protection And Over Voltage Protection
- 12 Preset Radio Station

- Full Remote Control
- VFD Display
- Power Output: 300W for L,R Channel (4 Ohm) 50W for Center, Surround L and Surround R(4 Ohm)
- Inout Selector: 3 Stereo RCA Selector, 1AM/FM Radio, 1 USB/SD, 2 Microphone Input
- Output: 5 Channel Speaker Output Terminal for L, R, sCenter, SL, SR, And 1 line Out for Subwoofer



UPC Number: 068889008661

PT980AUH

7.1 channel 350Watts Build-In AM/FM Radio /USB/SD card HDMI Amplifier Receiver

- 7.1 Channel Amplifier.
- 4 HDMI Input Port and 1 HDMI Output Port for HDMI Receiver and HDMI Switcher.
- One Key Switch Function Between HDMI Receiver and HDMI Switcher.
- Built-In AM/FM Radio.
- Built-In USB and SD Audio.
- 2 MIC Input, Treble and Bass of MIC Adjustable, Independent MIC Volume Control.
- Over Current Protection, Short Circuit Protection And Over Voltage Protection.
- 12 Preset Radio Station.

- Full Remote Control.
- VFD Display.
- Power Output: 300W for L,R Channel (4 Ohm) 50W for Center, Surround L and Surround R(4 Ohm) ,side Surround L and side Surround R(4 Ohm).
- Inout Selector: 4 in 1 out HDMI Selector, 3 Stereo RCA Selector, 1AM/FM Radio, 1 USB/SD, 2 Microphone Input.
- Output: 7 Channel Speaker Output Terminal for L, R, Center, SL, SR, RR, RL And 1 line Out for Subwoofe



UPC Number: 068889008678

PT598AS

5.1 Channel 350 Watt Digital Home Theater AM/FM Receiver Surround Sound Package w/ Subwoofer, Center Channel & 4 x Two Way Directional Satellite speakers

- 5.1 Channel Amplifier
- Built-In AM/FM Radio
- 2 MIC Input, Treble & Bass of MIC Adjustable, Independent MIC Volume Control
- Over Current Protection, Short Circuit Protection & Over Voltage Protection
- 12 Preset Radio Station
- Full Remote Control
- VFD Display
- Power Input: AC 115V 60Hz/230V 50Hz
- Power Output: 300W L,R Channel (4 Ohm); 50W for Center, Surround L & Surround R (4 Ohm)
- In-Out Selector: 3 Stereo RCA Inputs, AM/FM Radio, 1 DVD Input, 2 Microphone Inputs
- Output: 5 Channel Speaker Output Terminal for Left,

- Right, Center, Front Left, Front Right & Subwoofer
- Net Weight: 40.0 Lbs
- Gross Weight: 46.3 Lbs
- Box Dimensions: 25.2" x 20.3" x 16.5"
- Package Contents
- 1 x 5.1 Home Theater Receiver
- 1 x Amplifier Subwoofer
- 1 x Center Channel
- 4 x Satellite Two Way Directional Speakers
- Unit Dimensions
- 17"(H) x 13"(W) x 4.9"(D)
- 16.5" (H) x 15(W)" x 10.2"(D) 3.1" (H) x 4.7"(W) x 6.3"(D)
- 9.3" (H) x 4.7"(W) x 3.1"(D)



UPC Number: 068889008692

NEW PRODUCT FROM:

www.pyleaudio.com

PIWPD3

iPod/iPhone Wireless Speakers Docking Station with Aux Input

- Compatible player and charger for iPod/iPhone
- 2 Wireless Speakers with Built-In Rechargeable Lithium Batteries
- 3 Transmission Channels for Low Interference
- Speaker Power: 2x3 Watts
- 30 Meters (100 Feet) Transmission Range
- Volume Control Button on Each Speaker
- Changable Color Light on Each Speaker

- 3.5mm Aux-In Jack
- Video Out
- Automatic Tuning On Speakers
- Remote Control and 110-240V AC Adaptor Included



UPC Number: 068888999786

PHPNC45

High-Fidelity Noise-Canceling Headphones With Carrying Case

- Reduces Ambient Noise By 95%
- Ergonomically Designed For Maximum Comfortable Listening Experience
- Up To 20dB Of Noise Cancellation; Effectively Reduces Aircraft Or Subway Engine Noise
- Larger 40mm Driver With Clear Sound And Well Defined Bass
- Frequency Response: 30 20000 Hz
- Speaker Type: 40mm Mylar
- Cone Impedance: 32ohm

- Noise Reduced Over Frequencies 70 1200 Hz
- 2 X AAA Batteries Required
- Cable Length: Detachable 1.0m
- Connects With 3.5mm Stereo Jack
- Included Accessories: Detachable Audio Cable, 1/4-Inch Stereo-Plug Adapter, Dual-Plug Adapter (For Airplane), Hard Carry Case

