

NEW PRODUCTS FROM: **PYLE® 2011**

PCMM05 Carbon Monoxide Meter

- Digital LCD Display
- Auto/Manual Zero
- Fast Sampling
- Max Hold, Data Hold
- Auto Power Off
- Three Year Sensor Life
- Safety Alarm: Above 200ppm, Alarm Sounds Continuously
- Operating Temperature: 0-50° C
- Measurement Range: 0 to 1000 PPM
- Accuracy: +/- 15% or +/- 10 PPM
- Battery: 9V (Included)
- Sensor Type: Stabilized Electrochemical Gas-Specific (CO)
- Dimensions: 6.29" H x 2.17" W x 1.57" D
- Weight: 5.50 oz.

UPC Number: 068889006803



PCMT20 Digital AC/DC Auto-Ranging Clamp Meter

- Measures AC and DC
- Max. Resolution to Current Measurement: 0.1uA
- LCD Display with Backlight
- Data Hold, Zero Function, Auto Power Off
- Lower Battery Indicator
- 0.9" (23mm) Jaw Size
- DC Voltage: Range: 0-600V; Accuracy: +/- 0.5%
- AC Voltage: Range: 0-600V; Accuracy: +/- 1.5%
- AC Current: Range: 0-400A; Accuracy: +/- 3.0%
- Resistance: Range: 0-40 MΩ; Accuracy: +/- 3.0%
- Temperature: Range: 1000 °C / 1832 °F; Accuracy: +/- 3.0%
- Capacitance: Range: 100 uF; Accuracy: +/- 2.5%
- Frequency: Range: 150 kHz; Accuracy: +/- 1.2%
- Continuity: Buzzer Sounds at 100Ω
- Diode: Test Current 0.3mA; Open Circuit Voltage 1.5V
- Batteries: 2 x AAA Included
- Accessories Included: Black Bag, Test Leads, Type K Temperature Probe
- Dimensions: 8.07" H x 2.36" W x 1.18" D
- Weight: 7.94 oz.

UPC Number: 068889006834



PCTL01 Pipe Clamp Temperature Lead

- Clips On Pipe To Measure Temperature
- Plugs Into Meter
- Operating Temperature: -40 °F to 392 °F (-40 °C to 200 °C)
- Clamp Jaw Opening: 1 3/8" (6.5 cm)
- Length of Cord: 40" (102 cm)
- Dimensions: 5.12" H x 3.15" W x 1.02" D
- Weight: 3.07 oz.

UPC Number: 068889006810



PDMM01 Digital Manometer with 11 Units of Measure

- 11 Selectable Units of Measure (in H2O, Psi, Mbar, Bar, kPa, inHg, mmHg, Ozin2, ftH2O, cmH2O, KgCm)
- Display Max, Min, Average, with Relative Time
- Large LCD Backlit Dual Display
- Zeroing, Offset, and Data Compensation
- Low Battery Display and Automatic Shutdown
- Data Hold and Error Code
- Accuracy: +/- 0.3% FSO (25° C)
- Repeatability: +/- 0.2% (Max +/- 0.5% FSO)
- Linearity/Hysteresis: +/- 0.29% FSO
- Maximum Pressure: 10 PSI
- Response Time: 0.5 Sec.
- Power Supply: 9V Battery (Included)
- 2 Soft Hoses Included
- Dimensions: 6.69" H x 2.17" W x 1.30" D
- Weight: 5.82 oz.


UPC Number: 068889006797



PHHT15 Indoor Digital Hygro-Thermometer

- Indoor Relative Humidity and Comfort Level Indicator
- Clock Display with Alarm Function
- Selectable Celsius or Fahrenheit Display
- Temperature Range: -50° to 70° C / -58° to 158° F
- Temperature Accuracy: +/- 1° C (2° F)
- Humidity Accuracy: +/- 5%
- Humidity Display Resolution: 1%
- Sampling Period: 10s
- Battery: AAA, 1.5V (Included)
- Dimensions: 4.13" H x 3.94" W x 0.91" D
- Weight: 4.48 oz.

UPC Number: 068889006759



PIRT25 Compact Infrared Thermometer With Laser Targeting

- Unique Flat Surface
- Mini-Modern Housing Design
- Simple One-Handed Operation
- Laser Targeting
- LCD With Backlight
- Celsius or Fahrenheit Modes
- Laser On/Off Switch
- Automatic Power Off
- Display Hold Function
- Max/Min Function
- Temperature Range: -50 to 380 Celsius, -58 to 716 Fahrenheit
- Temperature Resolution: 0.1°
- Emissivity: Fixed at 0.95
- Optical Resolution: 8:1 Distance to Spot Size Ratio
- Basic Accuracy: +2% of Reading or +2 °C / +4 °F
- Response Time: <1 Sec.
- Diode Laser: Output <1mW @ 630-630nm, Class 11 Laser
- Spectral Response: 6-14um
- Power Supply: 9V Battery
- Dimensions: 7.09" H x 3.94" W x 1.81" D
- Weight: 5.6 oz.

UPC Number: 068889006711



www.pyleaudio.com

1600 63RD STREET . BROOKLYN, N.Y . 11204 . 718 535-1800 . 800 44-5671 . FAX: 718 236-2400

NEW PRODUCTS FROM: **PYLE® 2011**

PIRT30 High Temperature Infrared Thermometer with Type K Input

- Modern Housing Design
- Built-in Laser Pointer
- Type K Temperature Measurements
- 20 Point Memory
- Automatic Capture Emissivity for Targeting
- Laser Targeting
- LCD With Backlight
- Celsius or Fahrenheit Modes
- Laser On/Off Switch
- Automatic Power Off
- Display Hold Function
- Optical Resolution (Distance to Spot Size): 13:1
- Temperature Range: -50° to 550° C, -58° to 1022° F
- Temperature Resolution: 0.1°
- Type K Temperature Range: -50° to 1370° C, -58 to 2498° F
- Type K Temperature Resolution: 0.1° up to 2000, 1° over

UPC Number: 068889006728



PMIR15 Mini Infrared Thermometer with Laser Pointer

- Measure in Celsius or Fahrenheit
- Laser Targeting
- Data Hold, Max Hold
- Auto Power Off
- LCD Display
- Temperature Range: -50 to 280 °C / -22 to 518 °F
- Response Time: Less Than 750ms
- Resolution: 0.1 °C/°F
- Basic Accuracy: +/- 2%
- Optical Resolution: 6:1
- Battery: 2 x AAA, Included
- Dimensions: 3.74" H x 2.17" W x 1.18" D
- Weight: 2.61 oz.

UPC Number: 068889006827



PSPL03 Mini Sound Level Meter with A Frequency Weighting

- Max Hold Function
- Small Shape for Easy Portability
- Level Range: 35-100dB
- Accuracy: +/- 3dB (ref. 94dB @ 1kHz)
- Frequency Range: 31.5 Hz to 8 kHz
- Frequency Weighting: A
- Operation Temperature: 0 to 40°C (32 to 104° F)
- Storage Temperature: -10 to 60° C (14 to 140° F)
- Battery Type: 9V (Included)
- Dimensions: 6.69" H x 2.28" W x 1.38" D
- Weight: 3.77 oz.

UPC Number: 068889006780



PSPL25 Sound Level Meter with A and C Frequency Weighting

- Max Hold and Data Hold Function
- Auto Power Off
- Level Range: Low - 0-100dB, High - 60-130dB
- Accuracy: +/- 1.5dB (ref. 94dB @ 1kHz)
- Frequency Range: 31.5 Hz to 8 kHz
- Frequency Weighting: A and C Type
- Time Weighting: Fast, Slow
- Operation Temperature: 0 to 40°C (32 to 104° F)
- Operation Humidity: 10 to 90% RH
- Storage Temperature: -10 to 60° C (14 to 140° F)
- Storage Humidity: 10 to 75% RH
- Battery Type: 9V (Included)
- Dimensions: 9.06" H x 2.17" W x 2.17" D
- Weight: 7.20 oz.

UPC Number: 068889006773



PTHDL150 Temperature and Humidity Data Logger with USB Connection

- Selectable Measurement Cycle from 2 Seconds to 24 Hours
- Download Collected Data Through USB-to-PC Interface
- Analysis Software Runs on Windows 98, 2000, XP, Vista, 7
- Memory For Up To 16000 Readings
- 2 LEDs for Status Information
- Alarm for Minimum/Maximum Values
- Measuring Range: 0 to 100% RH, -40 to 70° C
- Accuracy: +/- 2% RH, +/- 1 °C
- Memory: 32000 Measurements (16000 Each for Temp./Humidity)
- Battery Life: 3 Years
- Includes 3.6 V Lithium Battery, CD-ROM with Software
- Dimensions: 3.94" H x 0.98" W x 0.79" D
- Weight: 1.13 oz.

UPC Number: 068889006766



PTHM15 Mini Temperature and Humidity Meter With Dew Point and Wet Bulb Temperature

- Auto Power Off
- Fast Response Time
- Dew Point Temperature
- Dual Display Temperature & Humidity
- Data Hold Function
- Humidity Range: 0-100%RH
- Temperature Range: -20° - 80° C / -4° - 176° F
- Dew Point Temperature: -20° - 80° C / -4° - 176° F
- Wet Bulb Temperature: 0°- 80° C / 32° - 176° F
- Humidity Accuracy: +/- 3% RH
- Air Temperature Accuracy: +/- 0.5° C @ 25° C
- Resolution: 0.01% RH, 0.01° C/F
- 40° F, <80% RH
- Dimensions: 6.89" H x 2.28" W x 1.38" D
- Weight: 5.04 oz.

UPC Number: 068889006742



PTHM20 Temperature and Humidity Meter With Dew Point and Wet Bulb Temperature

- Auto Power Off
- Fast Response Time
- Dew Point Temperature
- Dual Display Temperature & Humidity
- Data Hold Function
- Humidity Range: 0-100%RH
- Temperature Range: -30° - 100° C / -22° - 199° F
- Dew Point Temperature: -30° - 100° C / -22° - 199° F
- Wet Bulb Temperature: 0°- 80° C / 32° - 176° F
- Humidity Accuracy: +/- 2% RH
- Air Temperature Accuracy: +/- 0.5° C @ 25° C
- Operating Temperature: 32° F to 104° F, <80% RH
- Storage Temperature: 14°F to 140° F, <80% RH
- Dimensions: 8.98" H x 2.17" W x 1.30" D
- Weight: 6.77 oz.

UPC Number: 068889006735



www.pyleaudio.com

1600 63RD STREET . BROOKLYN, N.Y. 11204 . 718 535-1800 . 800 44-5671 . FAX: 718 236-2400